

















































HOLLOW STAINLESS-STEEL LEVER HANDLE ON ROUND OR SQUARE LEVER ROSE.

Features:

- Description: Stainless steel hollow lever handle set on round or square lever rose. Fully return spring assisted lever handle. The cylinder rose and lever rose features concealed fixing via an easy click.
- Material: stainless steel EN 1.4301 (type SUS304), optional in EN 1.4401 (type SUS316).
- Supplied with 8x8 mm spindle and fixing accessories.
- Door thickness: up to 50 mm (for doors thickness more than 50 mm please specify while ordering).
- Finishes: Satin Stainless Steel, Matt black or PVD satin brass or PVD polished brass. Other finishes are available upon request.

H01B01B	H01B01B SQ	H02B01B	H02B01B SQ
			
			
HL2B01B	HL2B01B SQ	H04B01B	H04B01B SQ
			
			

HL42B01B	HL42B01B SQ	H34B01B	H34B01B SQ
			
			
H30B01B	H30B01B SQ	H35B01B	H35B01B SQ
			
			
H36B01B	H36B01B SQ	H38B01B	H38B01B SQ
			
			

H31B01B	H31B01B SQ	B01.E1 B	B01Q.E1B
			
			
T07JQ-I01B	T07JQ01B	T01B01-8B	T01E01-8B
