

# INSTALLATION INSTRUCTIONS

## Art#: DC6224BCG

### CONCEALED DOOR CLOSER DOUBLE ACTION

Unit: mm

#### 1

**NOTE: HOLD OPEN FEATURE IS PROHIBITED ON FIRE RATED DOORS.**

1. The slider position should be away from the pivot side as shown.

#### 2

1. Locate the closer body as shown.  
2. For wood door, drill the hole by  $\varnothing 2.5$   
For steel door, drill the hole by  $\varnothing 4.2$  firstly and then tap the M5 thread

#### 3

① Turn the closing valve clockwise all the way until it stops.  
② Turn by 50°

#### 4

Connect the main arm and slider by provided screw

EN2	EN3	EN4
-6	0	+9

EN2	EN3	EN4
40Kg	60Kg	80Kg
850mm Max	950mm Max	1100mm Max

#### 5

Closing Control:

120°-15°

#### 6

Latch Control:

DP2 + DP5/2 IF CLOSER BODY IN FRAME OR LEAF.

DP5 IF CLOSER BODY IN LEAF.

15°-0°

#### 7

Back-check Control:

120°-15°

A backcheck cushion helps safeguard both the door and individuals behind it.

### ! Attention

When using the hold-open function, ensure the backcheck screw is fully open; otherwise, the door will not reach the hold-open position.

Do not operate the door closer beyond its maximum opening angle. A floor door stop or an alternative stop is strongly recommended.

This door closer contains a high-tension spring within the mechanism body. Do not attempt to dismantle the mechanism under any circumstances.

www.durablecollection.co.uk

210325 Page: 1/2

# INSTALLATION INSTRUCTIONS

## Art#: DC6224BCG

### CONCEALED DOOR CLOSER DOUBLE ACTION

Unit: mm

